

LCD SERIES

Floor Advertising Machine Single

65" Ultra HD High Brightness 3000 Nits Digital Signage



SUNLIGHT
VIEWABLE IMAGE




4K UHD
RESOLUTION



BUILT-IN
MEDIA PLAYER



THERMAL
MANAGEMENT



TRUECOLOR™
CALIBRATED

Android is a trademark of Google LLC.

The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License.

FOR MORE INFORMATION

SPECIFICATION

MODEL			650RJH-A
PANEL	LCD Panel Size	65 inch	
	Native Resolution	3840×2160	
	Brightness	3000 nits	
	Color Depth	1.07B	
	Contrast Ratio	1200:1	
	Response Time (Typ.)	8s	
	Viewing Angle	178/178	
	Light Lifetime (Typ.)	50000 Hours	
	Viewable With Polarized Lenses	Yes	
POWER	Power Supply	AC 100-240V 50/60Hz	
	Rated Voltage	AC 110V/230V	
	Power Consumption (Max.)	220W	
	Power Saving Mode	≤0.5W	
	AC Out	N/A	
MECHANICAL SPECS	Protection Glass	Yes (6T Tempered Glass IK10)	
	Cabinet Color	Default Black	
	Product Dimensions (LxHxD) mm	1123.0×2350.0×285.0	
	Monitor Weight	200kg	
	Orientation	Portrait	
	VESA Mounting (LxH) mm	N/A	
	Carrying Handles	Yes	
FEATURE	Language	Default English	
	Support SNMP (Up to V3.0)	N/A	
	Image Retention Protection	Yes	
	Auto Orientation Sensor	N/A	
	Ambient Light Sensor	N/A	
	Power On/Off Scheduling	Yes	
INPUT	OSD Menu Rotation	Yes	
	HDMI 2.0(HDCP 2.3)	HDMI input 4K 30/60Hz	
	DisplayPort 1.2	DP input 4K 60Hz	
	USB 3.0	USB 3.0×2	
OUTPUT	Micro SD Slot	Supports up to 32GB	
	Audio	Stereo Mini Jack	
ENVIRONMENT	Operating Temperature.	-10℃~ 45℃	
	Storage Temperature	-30℃~70℃	
	Humidity	10-95%(Non-condensing)	
	IP Rate	IP66	
INTERNAL PLAYER	Operating System	Android 11.0 or above	
	Processor	Quad-core Cortex-A55	
	Clock Speed	Up to 2.0GHz	
	Main Memory Interface	2GB LPDDR4 1.5GHz 64bit	
	Grapics	Supports OpenGL ES	
	Storage	16GB	
	Multimedia	4KP60 H.265/H.264/V/P9 video decoder 1080P60 H.264/H.265 video encode	
	Wireless Function	Wi-Fi 2.4/5.0GHz 802.11 a/b/g/n/ac/ax	
CERTIFICATION		CE/RoHS/FCC	

DIMENSIONS

Unit: mm [inch]

